

SAFETY DATA SHEET

Dimengel 100 base Page 1 of 9

Date of issue: 20/11/2014 Date of revision: 27/02/2019 Version no.: 3

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

<u>Product name:</u> Dimengel 100 base <u>Product description:</u> Photo curable resin

1.2 Relevant identified uses of the substance or mixture and uses advised against

Common uses: Printing/additive manufacturing.

1.3 Details of the supplier of the safety data sheet

N/A

E-mail address of person responsible for this SDS: N/A

1.4 Emergency telephone number

Emergency telephone number (with hours of operation): N/A

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to GHS:

Skin Irrit. 2 H315 Eye Irrit. 2A H319 Skin Sens. 1 H317 STOT SE 3 H335

Repr. 2 H361

Aquatic Acute 1 H400 Aquatic chronic 2 H411

Classification according to 29 CFR 1910.1200 (OSHA HCS):

Skin Irrit. 2 H315 Eye Irrit. 2A H319 Skin Sens. 1 H317 STOT SE 3 H335 Repr. 2 H361

Aquatic Acute 1 H400 Aquatic chronic 2 H411

Classification in accordance to Regulation (EC) No. 1272/2008 (CLP):

Skin irrit. 2 H315 Eye irrit. 2 H319 Skin Sens. 1 H317 STOT SE 3 H335 Aquatic Acute 1 H400 Aquatic chronic 2 H411

See section 16 for the full text of the H-statements declared above.

2.2 Label elements

<u>Labelling according to GHS:</u> <u>Hazard pictogram(s):</u>







Dimengel 100 base Page 2 of 9

Signal word: Warning

Hazard statement(s):

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H335: May cause respiratory irritation.

H361: Suspected of damaging fertility or the unborn child.

H400: Very toxic to aquatic life.

H411: Toxic to aquatic life with long lasting effects.

Precautionary Statement(s):

P202: Do not handle until all safety precautions have been read and understood.

P260: Do not breathe dust/fume/gas/mist/vapours/spray.

P264: Wash hands thoroughly after handling.

P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+313: If exposed or concerned: Get medical advice/attention.

<u>Labelling according to 29 CFR 1910.1200 (OSHA HCS)</u> <u>Hazard pictogram(s):</u>







Signal word: Warning

Hazard statement(s):

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H335: May cause respiratory irritation.

H361: Suspected of damaging fertility or the unborn child.

H400: Very toxic to aquatic life.

H411: Toxic to aquatic life with long lasting effects.

Precautionary Statement(s):

P202: Do not handle until all safety precautions have been read and understood.

P260: Do not breathe dust/fume/gas/mist/vapours/spray.

P264: Wash hands thoroughly after handling.

P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338: If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+313: If exposed or concerned: Get medical advice/attention.

<u>Labelling in accordance with Regulation 1272/2008 (CLP)</u> <u>Hazard pictogram(s):</u>





Dimengel 100 base Page 3 of 9

Signal word: Warning

Hazard statement(s):

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H335: May cause respiratory irritation.

H400: Very toxic to aquatic life.

H411: Toxic to aquatic life with long lasting effects.

Precautionary Statement(s):

P260: Do not breathe dust/fume/gas/mist/vapours/spray.

P264: Wash hands thoroughly after handling.

P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333 + P313: If skin irritation or rash occurs: Get medical advice/attention.

2.3 Other hazard

Not available

SECTION 3: Composition / information on ingredients

3.2 Mixtures:

Ingredient name	Identifiers	%	CLP Classification	GHS	OSHA HCS
				Classification	
Isobornyl acrylate	CAS number: 5888-33-5 EC number: 227-561-6	25-70	Skin Irrit. 2 H315 Eye Irrit. 2 H319 Skin Sens. 1B H317 STOT SE 3 H335 Aquatic Acute 1 H400 Aquatic chronic 2	Skin Irrit. 2 H315 Eye Irrit. 2A H319 Skin Sens. 1B H317 STOT SE 3 H335 Aquatic Acute 1 H400 Aquatic chronic 2	Skin Irrit. 2 H315 Eye Irrit. 2A H319 Skin Sens. 1B H317 STOT SE 3 H335 Aquatic Acute 1 H400 Aquatic chronic 2
Tricyclodecane dimethanol diacrylate	CAS number: 42594-17-2 EC number: 255-901-3	30-60	H411 Skin Sens. 1 H317 Aquatic Chronic 2 H411	H411 Skin Sens. 1 H317 Aquatic Acute 2 H401 Aquatic Chronic 2 H411	H411 Skin Sens. 1 H317 Aquatic Acute 2 H401 Aquatic Chronic 2 H411
Diphenyl(2,4,6- trimethylbenzoyl)p hosphine oxide	CAS number: 75980-60-8 EC number: 278-355-8	0.5-1	Repr. 2 H361f Aquatic Chronic 2 H411	Repr. 2 H361 Aquatic Chronic 2 H411	Repr. 2 H361 Aquatic Chronic 2 H411
Camphene	CAS number: 79-92-5 EC number: 201-234-8	<0.35	Flam. Sol. 2 H228 Eye Irrit. 2 H319 Aquatic Acute 1 H400 Aquatic Chronic 1 H410 M-Factor Chronic = 1	Flam. Sol. 2 H228 Eye Irrit. 2A H319 Aquatic Acute 1 H400 Aquatic Chronic 1 H410 M-Factor Chronic = 1	Flam. Sol. 2 H228 Eye Irrit. 2A H319 Aquatic Acute 1 H400 Aquatic Chronic 1 H410 M-Factor Chronic = 1
1,7,7- Trimethyltricyclo[2. 2.1.02,6]heptane	CAS number: 508-32-7 EC number: 208-083-7	<0.35	Eye Irrit. 2 H319 Aquatic Acute 1 H400 Aquatic Chronic 1 H410	Eye Irrit. 2A H319 Aquatic Acute 1 H400 Aquatic Chronic 1 H410	Eye Irrit. 2A H319 Aquatic Acute 1 H400 Aquatic Chronic 1 H410

Dimengel 100 base Page 4 of 9

2-Propenoic acid	CAS number:	≤0.12	Flam. Liq. 3 H226	Flam. Liq. 3 H226	Flam. Liq. 3 H226
	79-10-7		Acute Tox. 4 H302,	Acute Tox. 4 H302,	Acute Tox. 4 H302,
	EC number:		H332	H332	H332
	201-177-9		Skin Corr. 1A H314	Skin Corr. 1A H314	Skin Corr. 1A H314
			Eye Dam. 1 H318	Eye Dam. 1 H318	Eye Dam. 1 H318
			STOT SE 3 H335	STOT SE 3 H335	STOT SE 3 H335
			Aquatic Acute 1	Aquatic Acute 1	Aquatic Acute 1
			H400	H400	H400
			Aquatic Chronic 2	Aquatic Chronic 2	Aquatic Chronic 2
			H411	H411	H411

See section 16 for the full text of the H-statements declared above.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eyes contact: In case of contact with eyes, rinse immediately with plenty of soap and water for at

least 15 minutes. Get medical attention.

Skin contact: Take off contaminated clothing and shoes immediately. Wash off with plenty of water

for at least 15 minutes. Get medical attention.

Inhalation: Remove the victim from site of exposure to fresh air. If breathing is difficult, give

oxygen. If not breathing give artificial respiration. Get medical attention.

Ingestion: Do not induce vomiting. If victim is conscious, wash mouth thoroughly with water.

Never give anything by mouth to an unconscious person. Get medical attention.

4.2 Most important symptoms and effects, both acute and delayed

See section 2.2 (Label elements) and/or section 11 (Toxicological information) for the most important known symptoms and effects.

4.3 Indication of any immediate medical attention and special treatment needed

Not available

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable: Foam, carbon dioxide, dry chemical.

Not suitable: Solid water stream as it may scatter and spread fire.

5.2 Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating and toxic fumes.

5.3 Advice for firefighters

Special protective equipment for fire fighters: Fire fighters should wear full protective clothing and self-contained breathing apparatus in positive pressure mode. Cool containers exposed to flame with water spray until well after fire is out.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Ventilate area of spill.

Dimengel 100 base Page 5 of 9

6.2 Environmental precautions

Prevent entry into waterways, sewers, basements or confined areas.

6.3 Methods and materials for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations.

6.4 Reference to other sections

See Section 1 for emergency contact information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapors, spray, mist or gas. Wash thoroughly after handling. Handle in accordance with good industrial hygiene and safety practice.

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also section 8 for additional information measures. Avoid release to the environment.

7.2 Conditions for safe storage, including any incompatibilities

Storage: Keep container tightly closed in a dry, cool and well-ventilated place. Protect from heat, direct sunlight. Keep away from oxidizing agents, reducing agents, acids, bases, free radical generators, inert gas, oxygen scavenger, peroxides. An air space is required above the liquid in all containers; avoid storage under an oxygen-free atmosphere.

7.3 Specific end use(s): N/A

SECTION 8: Exposure control/personal protection

8.1 Control parameters

Occupational exposure limits values: N/A

8.2 Exposure controls

Engineering measures

Use process enclosures, local exhaust ventilation, or others engineering controls to keep airborne levels below recommend exposure limits. If user operations generate dust, fume or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit.

Person Protective measures

<u>Respiratory protection:</u> Suitable respirator. Be sure to use an approved/certified equipment or equivalent equipment. Wear appropriate respirator when ventilation is inadequate.

Hand protection: Wear protective gloves to prevent skin exposure.

Eye protection: Wear protective safety glasses.

Skin protection: Wear appropriate long-sleeved clothing to minimize skin contact.

Environmental exposure controls: Not available

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance: transparent-white thick liquid-gel

Odour: characteristic Odour threshold: N/A

pH: N/A

Melting point/Freezing point: N/A

Dimengel 100 base Page 6 of 9

Initial boiling point/boiling range: N/A

Flash point: N/A Evaporation rate: N/A Flammability: N/A

Upper/lower flammability or explosive limits: N/A

Vapor pressure: N/A Vapor density: N/A Relative density: N/A Solubility(ies): N/A

Partition coefficient Octanol/Water: N/A

Auto-ignition temperature: N/A Decomposition temperature: N/A

Viscosity: N/A

Explosive properties: N/A Oxidizing properties: N/A

9.2 Other information:

N/A

SECTION 10: Stability and reactivity

10.1 Reactivity

Not available

10.2 Chemical stability

The product is stable under normal handling and storage conditions described in Section 7.

10.3 Possibility of hazardous reactions

Hazardous reactions are not expected, under normal conditions of storage and use.

Polymerization is exothermic and can degenerate into an uncontrolled reaction.

Inhibitors have been added to stabilize isobornyl acrylate. Maintaining air in the storage containers is important to keep inhibitors active. Unless inhibited, hazardous polymerisation may occur.

Tricyclodecane dimethanol diacrylate may polymerize.

10.4 Conditions to avoid

Heat, direct sunlight, ultraviolet light.

10.5 Incompatible materials

Oxidizing agents, reducing agents, acids, bases, free radical generators, inert gas, oxygen scavenger, peroxides.

10.6 Hazardous decomposition products

Other decomposition products: not available

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity:

Product/ingredient name	Test	Species	Dose
Isobornyl acrylate	LD50, Oral	Rat	4890 mg/kg
	LD50, Administration onto the skin	Rabbit	>5000 mg/kg
Diphenyl (2,4,6-trimethylbenzoyl) phosphine oxide	LD50, Oral	Rat	>5000 mg/kg

Skin corrosion/irritation: Not available

Serious eye damage/irritation: Not available

SAFETY DATA SHEET

Dimengel 100 base Page 7 of 9

Respiratory or skin sensitization: Not available

Germ cell mutagenicity: Not available

Carcinogenicity: Not available

Reproductive toxicity: Not available

Specific target organ toxicity (single exposure): Not available

Specific target organ toxicity (repeated exposure): Not available

Aspiration hazard: Not available

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
Diphenyl (2,4,6-trimethylbenzoyl) phosphine oxide	IC50/72h, 1-10 mg/l	LC50/96h, 1-10 mg/l	EC50/48h, 1-10 mg/l
Isobornyl acrylate	ErC50/72 h (Pseudokirchneriella subcapitata) 1.98 mg/l NOECr/72 h (Pseudokirchneriella subcapitata) 0.405 mg/l	LC50/96h (Danio rerio (zebra fish)) 0.7 mg/l	NOEC/21d (Daphnia magna (Water flea)) 0.092 mg/l

12.2 Persistence and Degradability

Isobornyl acrylate

Not readily biodegradable: 57% after 28 d.

12.3 Bioaccumulative potential

Isobornyl acrylate

Partition coefficient: n-octanol/water: log Kow: 4.52, Potentially bioaccumulable.

12.4 Mobility in soil

Not available

12.5 Results of PBT and vPvB assessment

Not available

12.6 Other adverse effects

Very toxic to aquatic life. Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste must be disposed of in accordance with federal, state and local environmental control regulations.

<u>Packing</u>

Empty containers should be taken for local recycling, recovery or waste disposal.

SECTION 14: Transport information

14.1 Un number

<u>ADR/RID:</u> 3082 <u>IMDG:</u> 3082 <u>IATA:</u> 3082 <u>DOT (US):</u> 3082

Dimengel 100 base Page 8 of 9

14.2 UN proper shipping name

<u>ADR/RID:</u> ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ISOBORNYL ACRYLATE)

IMDG: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ISOBORNYL ACRYLATE)

<u>IATA:</u> Environmentally hazardous substance, liquid, n.o.s. (Isobornyl acrylate)

<u>DOT (US):</u> ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ISOBORNYL ACRYLATE)

14.3 Transport hazard class(es)

<u>ADR/RID</u>: 9 <u>IMDG</u>: 9 <u>IATA</u>: 9 <u>DOT (US)</u>: 9

14.4 Packing group

ADR/RID: III IMDG: III IATA: III DOT (US): III

14.5 Environmental hazard

Marine pollutant: yes

14.6 Special precautions for user

N/A

14.7 Transport to bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not available

SECTION 15: Regulatory information

This SDS complies with the following requirements of:

EU Regulation (EC) No.1907/2006 (REACH) including amendments

Regulation (EC) No.1272/2008 (CLP)

29 CFR 1910.1200 (OSHA HCS)

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

California Prop. 65 Components

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm. (Benzene, methyl- $108-88-3 \le 0.6\%$)

TSCA inventory

The substances in this product are included on or exempted from the TSCA inventory.

15.2 Chemical safety assessment

Not available

SECTION 16: Other information

HMIS Rating

Health hazard: 2 Chronic Health Hazard: * Flammability: 0 Physical Hazard: 0

NFPA Rating

Health hazard: 2 Flammability: 0 Instability: 0

Full text of Hazards Statements referred to in sections 2 and 3:

Flam. Liq. - Flammable liquid

Flam. Sol. - Flammable solid

Acute Tox. - Acute toxicity

Skin Irrit. - Skin irritation

Skin Sens. - Skin sensitization

Dimengel 100 base Page 9 of 9

Eye Irrit. - Eye irritation

Skin Corr. - Skin corrosion

Eye Dam. - Serious eye damage

STOT SE - Specific target organ toxicity — single exposure

Repr. - Reproductive toxicity

Aquatic Acute - Hazardous to the aquatic environment Aquatic Chronic - Hazardous to the aquatic environment

H228: Flammable solid.

H226: Flammable liquid and vapour.

H302: Harmful if swallowed.

H332: Harmful if inhaled.

H314: Causes severe skin burns and eye damage.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H318: Causes serious eye damage.

H319: Causes eye irritation.

H335: May cause respiratory irritation.

H361: Suspected of damaging fertility or the unborn child.

H361f: Suspected of damaging fertility.

H400: Very toxic to aquatic life.

H401 Toxic to aquatic life.

H410: Very toxic to aquatic life with long lasting effects

H411: Toxic to aquatic life with long lasting effects.

Training advice: Before using/handling the product one must read carefully present SDS.

Key Legend Information:

CAS- Chemical Abstract Service

ACGIH- American Conference of Governmental Industrial Hygienists

OSHA- Occupational Safety and Health Administration

NTP- National Toxicology program

IARC- International Agency for Research on Cancer

N/A- Not available

H-statements- Hazard statements

TLV- Threshold Limit Value

TWA- Time-weighted average

STEL- Short-Term Exposure Limit

CSA- Chemical safety assessment

This SDS and the information presented within it are based on data held by Hazmat, Ltd. and the current legislation as at the date stated on it. Anyone wishing to make use of the information presented within this document is obligated to update its instructions from time to time. The information presented in the SDS is based on the manufacturer's data and/ or the supplier of the substance/ product which is the subject of this SDS, as provided to Hazmat, Ltd. by the client and in the absence of such data the information was taken from a variety of literary professional sources. The information presented in this SDS is appropriate for the uses specified in paragraph 1 of the SDS only. It is emphasized, that the information specified in this SDS does not replace specific safety instructions for uses of the substance/ product which is the subject of this SDS, which were not explicitly specified in the SDS. Individual professional consultation should be received, and specific safety instructions should be read prior to any mixing of the substance which is the subject of this SDS with other substances and the stated in this SDS does not cover the entire safety instructions relating to mixing the substance which is the subject of this SDS with other substances and does not constitute a replacement to obtaining specific consultation as stated. Hazmat, Ltd. is not liable to any damage and/ or any loss, financial or otherwise, and will not accept responsibility, directly or indirectly, to damages of any kind, including as a result of failure to update and/ or misunderstanding and/ or misuse/ misinterpretation of the information within the document. Any question arising regarding the use of the SDS should be directed to Hazmat, Ltd., 19 Ha'Melacha st. Rosh Ha'Ayin, Tel: +972-3-9037141, fax: +972-3-9032717, email: hazmat@hazmat.co.il.

The information detailed in this SDS was prepared by Hazmat, Ltd. for the orderer of the SDS and is for their use only. The contents of this SDS is the property of Hazmat, Ltd. only and it is strictly prohibited to copy, modify, edit, distribute, sell or take any other action which involves infringement of Hazmat's copyrights without the prior written consent of Hazmat, Ltd.

Version	Date	Prepared by	Quality Auditor
2	20/12/2017	D.A	K.B
3	27/02/2019	K.B	M.H